Unfriend your Boss

Mapping Organizations Social Networks for Red Team Engagments

HamburgSides 2016 - Quentin Kaiser (@qkaiser)



who?

- Quentin Kaiser
- Security Engineer / Penetration Tester
- contact@quentinkaiser.be
- **\$** @qkaiser
- A https://qkaiser.github.io

Disclaimer

This research was prepared and accomplished in my personal capacity. The opinions expressed in this talk are my own and do not reflect the view of past, current, or future employer.

Agenda

- The Origins
- Scraping Facebook 101
- Social Network Analysis
- Leveraging results during red team gigs
- Possible developments
- Mitigating Exposure

When it comes to phishing, most pentest shops do it like this:

When it comes to phishing, most pentest shops do it like this:

• scraping emails off the Internet

When it comes to phishing, most pentest shops do it like this:

- scraping emails off the Internet
- finding profiles, finding email pattern, generating addresses

When it comes to phishing, most pentest shops do it like this:

- scraping emails off the Internet
- finding profiles, finding email pattern, generating addresses
- hit "send"

When it comes to phishing, most pentest shops do it like this:

- scraping emails off the Internet
- finding profiles, finding email pattern, generating addresses
- hit "send"

That's cool, but does it really reflect advanced attackers?

I want to fully take advantage of social **networks**

Research Questions

- how much data is exposed by an organization members through social media?
- what information can be derived from such data?
- how can we exploit that information in red team gigs?

Enter Facebook Graph Search

Facebook Graph Search

- Semantic search engine
- Introduced back in March 2013
- User send query in natural language to search for entities such as pages, places, events, check-ins, status updates, and people

Facebook Graph Search

Facebook thwarted privacy concerns around Graph Search, explaining that entities are indexed based on privacy settings that Facebook users can tweak.


Facebook Graph Search

- Using the privacy settings as an argument for privacy protection is a fallacy.
- if *some* members of a graph under scrutiny are sharing their relationships publicly, each person linked to that overly open person will be included in the graph. Even if they don't want to.
- you decide attributes you share, not relations

Methodology


- 1. Scrape data off Facebook
- 2. Store it in graph database
- 3. Apply SNA
- 4. Exploit

The Stack



- wrote a scraper in Python based on initial work with recon-ng
- Facebook's continuous integration continuously breaks it
- but when it works

1. Find company page




2. Employees retrieval



/search/C_ID/employees/present

3. Relationships retrieval



/search/C_ID/employees/present/U_ID/friends/intersect

User-Agent blacklisting

- User-Agent blacklisting
- Session token


- User-Agent blacklisting
- Session token
- Lazy Loading

- User-Agent blacklisting
- Session token
- Lazy Loading
- Parsing

- User-Agent blacklisting
- Session token
- Lazy Loading
- Parsing
- Rate limiting

- User-Agent blacklisting
- Session token
- Lazy Loading
- Parsing
- Rate limiting
- CAPTCHA

Data Acquistion Results



Data Acquisition Results

- data set comprised 20 large companies with > 10k employees
- coverage oscilate around 20%
- 3000 nodes per company on average

Data Acquisition Results

- data set comprised 20 large companies with > 10k employees
- coverage oscilate around 20%
- 3000 nodes per company on average

Data is incomplete and I don't have the processing power of a server farm.

Data Acquisition Results

- data set comprised 20 large companies with > 10k employees
- coverage oscilate around 20%
- 3000 nodes per company on average

Data is incomplete and I don't have the processing power of a server farm.

lt's therefore qualitative analysis.

Degree Centrality

- Degree Centrality
- Betweenness Centrality

- Degree Centrality
- Betweenness Centrality
- Community Detection

- Degree Centrality
- Betweenness Centrality
- Community Detection
- Hierarchy Reconstruction

Social Network Analysis

- Degree Centrality
- Betweenness Centrality
- Community Detection
- Hierarchy Reconstruction

SNA / Degree Centrality

Degree centrality is a measure of influence within large and complex networks.

SNA / Degree Centrality

Nodes with highest degree:

- HR department workers
- union representatives
- "social beasts"

SNA / Betweenness Centrality

A measure for quantifying the control of a human on the communication between other humans in a social network.


SNA / Betweenness Centrality


Nodes with highest degree are high value targets holding coordinators profiles (executives, directors).

SNA / Betweenness Centrality

Nodes with highest degree are high value targets holding coordinators profiles (executives, directors).

Really close to a "executives top 10".







SNA / Community Detection

Humans have a tendency to homophily, mainly caused by geographical and organizational foci. Such a tendency can be visualized when applying community detection algorithms to the acquired social networks.

SNA/ Community Detection

- Relied on Louvain algorithm
- Observed communities foci:
 - geographical locations
 - internal departments
- could potentially identify hidden communities
 - internal commissions
 - working groups
 - shared common interest (sports club, political affiliation)





SNA/ Community Detection

SNA / Hierarchy Reconstruction

Hierarchy reconstruction can't be done because edges are **not** weighted and undirected.

SNA / Hierarchy Reconstruction

Hierarchy reconstruction can't be done because edges are **not** weighted and undirected. **?**

Leveraging results during red team gigs

- phishing on steroid
- social engineering tactics
- emulating corporate espionage
- organizational destabilization

Possible developments

- extension to other online social networks
- inclusion of profile attributes
 - geolocation (home town, work address, geolocated posts, checkins)
 - time (employmentship duration, friendship duration)

Methodology could be applied to Twitter.

- 1. find target organization twitter profile
- 2. search profiles mentioning @org in their bio
- 3. get relationships by intersecting each member's followers with profiles set

I actually did it.

```
qkaiser@localhost$ python main.py tesla
[+] Connecting to Neo4J ...
[+] Connection established (Neo4J 2.2.5)
[+] Searching for tesla ...
    [0] TeslaMotors
    [1] elonmusk
    [2] TeslaMotorsClub
Please select a profile:0
Looking for @TeslaMotors employees...
```

Some kind of NLP is required to differentiate:

Some kind of NLP is required to differentiate:

fan boys

```
[*] ChrisLaylin - Aspiring @TeslaMotors owner
[*] dpetersson - early adopter & @TeslaMotors fan
```

Some kind of NLP is required to differentiate:

fan boys

```
[*] ChrisLaylin - Aspiring @TeslaMotors owner
[*] dpetersson - early adopter & @TeslaMotors fan
```

ex-employees

```
[*] JordanLevine - Former: @TeslaMotors
[*] clairissima - formerly @teslamotors
```

Some kind of NLP is required to differentiate:

fan boys

```
[*] ChrisLaylin - Aspiring @TeslaMotors owner
[*] dpetersson - early adopter & @TeslaMotors fan
```


• ex-employees

```
[*] JordanLevine - Former: @TeslaMotors
[*] clairissima - formerly @teslamotors
```

actual employees

```
[*] rcpopple - Finance Director @TeslaMotors
[*] markmuraoka - Battery Engineering Intern @TeslaMotors
```

- broadcast-oriented networks
- not enough coverage
- still, can enrich prior analyis 🍃



It is difficult to safely reveal limited information about a social network

 Joseph Bonneau in "Eight friends are enough: Social graph approximation via public listings."

- Facebook
 - exposure limitation as function of node distance
 - anti-scrapping measures

- Organizations
 - find a balance between PR benefit and potential threat of exposure
 - legal department issue
 - security awareness training

- End users
 - o remove as much information as possible

I haz find bug, pls send 500\$

I didn't get in contact with FB because of this:

This is a case where privacy can get complicated [...]. We've chosen to focus more on privacy controls around your content and personal information, since trying to maintain privacy by limiting discoverability is often an illusion. Since Facebook is a network designed for social participation, it's nearly impossible for it to work properly and let people stay completely hidden - there are many ways to discover a profile or friendship beyond friend lists or searches. But even if someone discovers your profile, you have a great degree of control about what they can then access.

Facebook bug bounties - the unofficial treasure map, June 2016. https://www.facebook.com/notes/phwd/facebook-bug-bounties-the-unofficial-treasure-map/1020506894706001

Thanks for your attention!

Any questions?

Links! Links! Links!

Toolkit https://github.com/qkaiser/segraph

(code broke again, I'll push it as soon as I fixed it.)

- Blog post https://qkaiser.github.io/
- White paper https://qkaiser.github.io/publications

Related Work

aka "cool reads"

- The Power of Local Information in Social Networks by Borgs et al.
- Inferring the Maximum Likelihood Hierarchy in Social Networks by Maiya et al.
- Finding Hierarchy in Directed Online Social Networks by Gupte et al.
- Eight Friends Are Enough: Social Graph Approximation via Public Listings by Bonneau et al.

Food for thoughts



WORLD NEWS | Sat Dec 24, 2016 | 9:52am EST

Turkish authorities investigating 10,000 social media users: ministry



Guess how.